



MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking. Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron, etc. Characteristics: compact and light \* high welding current stability in spite of mains voltage fluctuations \* arc force, hot start and anti-stick devices \* thermostatic, overvoltage, undervoltage, overcurrent, motorgenerator (+/-15%) protections. Complete with MMA welding accessories and aluminium carry case.



PROFESSIONAL



**HIGH PERFORMANCES!**  
**HEAVY DUTY**  
**USE 100%**

<p>COMPLIANCE WITH NEW CE MARKING</p>	<p>SUPPLY WITH MOTOGENERATORS (VIN +/-15%)</p> <p>MOTOGENERATOR POWER - SOURCE</p>	<p>INTENSIVE USE</p>	<p>FIT WITH ACCESSORIES AND ALU CARRY CASE</p>	<p>BASIC AND RUTILE ELECTRODES</p> <p><b>RUTILE BASIC</b></p>
---------------------------------------	--	----------------------	--	---

Norms:	LVD: EN 60974-1	LVD: EN 50445	EMC: EN 60974-10						
CODE	V <sub>ph</sub> V50/60Hz	A <sub>MIN</sub> A	A <sub>MAX</sub> 40°C A EN60974-1	A <sub>60%</sub> 40°C A EN60974-1	V <sub>o</sub> V	A <sub>60%</sub> I <sub>MAX</sub> A	P <sub>60%</sub> MAX kW	P <sub>GEN</sub> kW	η n%
816206	230 1 ph	5 180 DC	180 30 % DC	125 DC	83 DC	23 35	3,5 5,5	8	87
cosphi	Ø <sub>E</sub> MIN MAX DC mm	IP	W <sub>H</sub> L cm(L,W,H)	kg	BAR CODE	pz/pallet			
0,7	1,6 4	IP23	36 40 18,5	8,4	8004897810 04 1	30			