

TIG (high frequency HF or LIFT striking) and MMA inverter welding machine in direct current (DC). Use with a wide range of materials such as steel, stainless steel, titanium, copper, nickel and their alloys. Characteristics: TIG regulations: current down slope, bi-level \* MMA regulations: arc force according to the type of electrode in use \* 2/4 strokes operation \* hot start and anti-stick devices \* remote control connector \* MMA electrodes: rutile, basic, stainless steel and cast iron \* thermostatic, overcurrent, overvoltage, undervoltage protections. The optional TIG PULSE allows pulse welding. Complete with TIG welding accessories.



PROFESSIONAL



Norms:	LVD: EN 60974-1	LVD: EN 50445	EMC: EN 60974-10						
CODE	V <sub>ph</sub> V50/60Hz	A <sub>MIN</sub> A	A <sub>MAX</sub> 40°C A EN60974-1	A <sub>60%</sub> 40°C A EN60974-1	V <sub>o</sub> V	A <sub>60%</sub> I <sub>MAX</sub> A	P <sub>60%</sub> MAX W	η n%	φ cosphi
852032	230 1 ph	5 220 DC	220 30 % DC	125 DC	87 DC	24 33	3,6 5,5	83	0,7
Ø <sub>MIN</sub> E <sub>MAX</sub> DC mm	IP	W <sub>H</sub> L cm(L,W,H)	kg	BAR CODE					
1,6 4	IP23	38,5 15 36	13,3	8004897812 12 0					