

MMA and TIG inverter, electrode welding machine in direct current (DC) with scratch striking. Designed for welding cellulosic electrodes and coated electrodes such as aluminium, rutile, basic, stainless steel and cast iron electrodes with diameter up to 4 mm. It can be connected to motorgenerators. Characteristics: compact and light * high welding current stability in spite of mains voltage fluctuations * arc force, hot start and anti-stick devices * thermostatic, overvoltage, undervoltage, overcurrent protections * multiprotections for motorgenerators. Complete with MMA welding accessories and aluminium carry case.



PROFESSIONAL



COMPLIANCE WITH NEW CE MARKING



HIGH DUTY CYCLE



HIGH PERFORMANCES

INPUT MULTIPLE PROTECTIONS



REGULATION ARC FORCE, HOT START



WIDE RANGE OF ELECTRODES



CELLULOSIC,
ALUMINIUM,
STAINLESS STEEL,
RUTILE, BASIC,

Norms:		LVD: EN 60974-1		LVD: EN 50445		EMC: EN 60974-10			
CODE	V _{ph} V50/60Hz	A _{MIN} A	A _{MAX} 40°C A EN60974-1	A _{60%} 40°C A EN60974-1	V _o V	A _{60%} A _{MAX} A	P _{60%} P _{MAX}	P _{GEN} kW	η n%
816213	230 1 ph	5 180 DC	180 35 % DC	140 DC	102 DC	27 36	4,3 6	9	84
cosphi	Ø _{MIN} Ø _{MAX} mm	IP	W _H cm(L,W,H)	kg	BAR CODE	pz/pallet			
0,7	1,6 4	IP23	35,5 46,5 18,5	10,1	8004897828 73 2	30			