
## **66A - METRIC HINGED COMBINATION WRENCHES**



## **Description :**

• Hinged socket wrenches: the socket can be turned by 180° for maximum access.

- The socket is held in position tanks spring locking.
- OGV® profile with 12-point ring for powerful tightening while protecting the nut.
- Metric sizes: 6 to 32 mm.
- Presentation: satin chrome finish.



## **References :**

Ð	A [mm]	B x B1 [mm]	C x C1 [mm]	H x H1 [mm]	L [mm]	L1 [mm]	[g]	C1 [mm]
66A.6X7	6x7	10,3 x 11,5	15 x 15	23,0 x 23,0	188,5	156	95	
66A.8X9	8x9	12,6 x 13,85	15 x 15	23,0 x 23,0	188,5	156	100	
66A.10X11	10x11	15,0 x 16,5	18 x 18	26,0 x 26,0	194,5	156	105	
66A.10X13	10x13	15,0 x 19,0	21 x 21	31,0 x 31,0	233,5	189,5	190	
66A.12X13	12x13	17,5 x 19,0	21 x 21	31,0 x 31,0	233,5	189,5	195	
66A.14X15	14x15	20,5 x 21,75	23 x 23	33,0 x 33,0	237,5	231	215	

FACOM											
	Ð	A [mm]	B x B1 [mm]	C x C1 [mm]	H x H1 [mm]	L [mm]	L1 [mm]	[g]	C1 [mm]		
	66A.16X17	16x17	23,0 x 24,0	23 x 23	35,0 x 35,0	280,0	231	325			
	66A.16X18	16x18	23,0 x 24,7	23 x 24	35,0 x 36,0	281,0	231	330	23		
	66A.18X19	18x19	24,7 x 26,0	24 x 28	36,0 x 40,0	286,0	231	345			
	66A.21X23	21x23	28,6 x 31,5	28 x 30	41,5 x 43,5	331,0	270	535			