



LED / Focus configuration:		1 CREE Power Chip / Sliding Hyperfocus™
Case Material / Surface Tre	atment:	Anodized, High Strength Aluminium
Case Color:		Anthracite Dark Grey
Switch:	Q	uality Tested Metal Switch With Touch Function - Switch At Rear
Dimensions:		L: 115.3mm, ø: 26.5mm
Weight incl. battery:		99g
Ingress Protection Rating:		Splash Waterproof IPx4
Temperature:		-20°C to +50°C
Built in Controller:		YES, 5-step controller by press or touch
Standard Power Source:		3 x AAA Alkaline
Compatible with rechargea	ble cells:	YES, with AAA NiMh 1.2V
Beam / Distance:		Variable from Spot to Floodlight / 230 Meters
Luminous Flux:	Max: 380 lm	n / High: 200 lm / Medium: 50 lm / Low: 15 lm / Stroboskop 10 Hz
Lighting Time:		Max: 2h 15min / High: 2h 45min / Medium: 12h / Low: 60h
Accessories included:		Pro. Quality Pouch with Velcro and Press Stud, Strap
Customs Tariff Number:		8513 1000
Packaging:		Presentation tube
Single Box Content / Size / Weight:		1 pcs, height/diameter, 18 x 8.5 cm / 328 g
Master Box Content / Size / Weight:		32 pcs, 35.5 x 36 x 39 cm / 8.1 kg
Order's Adress:		info@suprabeam.com

Barcode and part number, varies by language, contact Suprabeam for information.

