

LED / Focus configuration:	1 CREE Power Chip / Sliding Hyperfocus™
Case Material / Surface Treatment:	Anodized, High Strength Aluminium
Case Color:	Anthracite Dark Grey
Switch:	Quality Tested Silicone Switch With Touch Function - Switch At Rear
Dimensions:	L: 150mm, ø: 46mm
Weight incl. battery:	307g
Ingress Protection Rating:	Splash Waterproof IPx4
Temperature:	-20°C to +35°C
Built in Controller:	YES, 5-step controller by press or touch
Standard Power Source:	Li-ion 26650 (18.5 Wh) 2 pcs. included
Beam / Distance:	Variable from Spot to Floodlight / 345 Meters
Luminous Flux: Max:	1000 lm / High: 500 lm / Medium: 250 lm / Low: 50 lm / Strobe 10 Hz
Lighting Time:	Max: 2h 45min / High: 3h 35min / Medium: 8h / Low: 37h
Accessories included:	Pro. Quality Pouch with Velcro and Press Stud, Strap,
	100-240VAC Adaptor with USB cable and external ICR 26650 Charger
Customs Tariff Number:	8513 1000
Packaging:	PE Portable Box with Space for Second Battery
Single Box Content / Size / Weight:	1 pcs, 28 x 23 x 8 cm / 1.3 g
Master Box Content / Size / Weight:	6 pcs, 41 x 41 x 27.5 cm / 7.1 kg
Order's Adress:	info@suprabeam.com

Barcode and part number, varies by language, contact Suprabeam for information.

