# 3M<sup>™</sup> PELTOR<sup>™</sup> Level Dependent Earplug, LEP-200 EU

# **Product Description**

The 3M<sup>™</sup> PELTOR<sup>™</sup> Level Dependent Earplug helps protect your hearing, and can help improve situational awareness and communications in challenging environments. Integrated with level-dependent technology, the LEP-200 helps provide hearing protection in noise and situational awareness in quiet environments. Ear pieces also include a small antenna to allow audio signals to be received wirelessly from a neckloop accessory sold separately.

ELTOF

# **Key Features**

- Helps provide hearing protection
- Level-dependent function (for ambient listening)
- Intuitive one-button operation
- Rechargeable
- Allow audio signals to be received wirelessly from a neckloop accessory

# Applications

Construction, Maintenance, Manufacturing, Hunting / Shooting.

## **Standards and Approvals**

3M Svenska AB hereby declares that this 3M<sup>™</sup> PELTOR<sup>™</sup> Headset is in compliance with the essential requirements and other provisions set out in the appropriate directives. Thereby they fulfil the requirements for CE marking.

Hereby, 3M Svenska AB declares that the radio equipment type ambient listening device is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address: http://www.3M.com/peltor/doc The product has been tested and approved in accordance with [EN 352-2:2002, EN 352-7:2003, prEN352-9]. Additional information can be obtained by contacting 3M in the country of purchase or 3M Svenska AB, SE 33102 Värnamo, Sweden. For contact information, see last pages of this user instruction. This product contains electrical and electronic components and must not be disposed of using standard refuse collection. Please consult local directives for disposal of electrical and electronic equipment. Notified Body Type Examination Certificate acc. directive 89/686/EEC: PZT GmbH, An der Junkerei 48 F, D-26389 Wilhelmshaven,Germany. Notify body #1974

# Models:

| Article number | Description  | 3M ID number   |
|----------------|--|----------------|
| LEP-200 EU     | 3M™ PELTOR™ LEP-200 EU Level Dependent Earplug Kit | 70-0716-7702-8 |

### **Accessories and Spare parts**

| TEP-CORD       | 3M™ PELTOR™ Tactical Earplug Replacement Cord                     | 7100074090     |
|----------------|---|----------------|
| TEP-LOOP-200   | 3M™ PELTOR™ Neckloop  | 70-0716-7703-6 |
| LEP-200E       | 3M™ PELTOR™ Replacement Earpiece                                  | 70-0716-7704-4 |
| LEP-100C       | 3M™ PELTOR™ LEP Earplug Replacement Case                          | 70-0716-7513-9 |
| 370-TEPL-25    | 3M™ UltraFit™ Communication Tips Replacement,<br>Large, 25 pairs  | 70-0716-7374-6 |
| 370-TEPM-25    | 3M™ UltraFit™ Communication Tips Replacement,<br>Medium, 25 pairs | 70-0716-7373-8 |
| 370-TEPS-25    | 3M™ UltraFit™ Communication Tips Replacement,<br>Small, 25 pairs  | 70-0716-7372-0 |
| PELTIP5-01     | 3M™ Torque™ Eartips, 50 pairs                                     | XH001679626    |
| CCC-GRM-25     | 3M <sup>™</sup> PELTOR <sup>™</sup> Communication Tip             | 70-0716-7521-2 |
| TEP-WINDSCREEN | 3M™ PELTOR™ TEP/LEP WINDSCREEN FOAM                               | 70-0716-7590-7 |







# **Technical data specifications**

3M<sup>™</sup> PELTOR<sup>™</sup> Level Dependent Earplug, LEP-200 EU

# **Technical data specifications**

| Model                          |                            |
|--------------------------------|----------------------------|
| Microphone Type                | Omni-directional           |
|                                |                            |
| Earplug Power / Electrical Cha | racteristics               |
| Earplug Battery Type:          | Lithium Ion                |
| Earplug Battery Life:          | Up to 16 hours             |
| Earplug Battery Charge Time:   | Approximately 90 minutes   |
| Earplug Volume Steps:          | 3 steps, Low, Normal, High |
| Case Battery Type:             | 3 AA Alkaline Batteries    |
| Case Battery Life:             | Up to 16 recharging cycles |
| Case USB Type:                 | Micro B                    |

# Standards

| Waterproof Rating: | Complies with IP54 with cover and USB port closed. |
|--------------------|--|
| SNR                | PPE directive 89/686/EEC                           |

# **Physical Characteristics**

| Case Size (L x W x H):   | 114.2 mm x 78.2 mm x 26.9 mm   |
|--|--------------------------------|
| Case Material:   | ABS                            |
| Earplug Keypad:  | One button operation           |
|  | (On / Off / Mode Selection)    |
| Case Keypad:   | One button operation (Charging |
|  | Status)                        |
| RoHS Compliance:   | RoHS II                        |
| Weight Box containing charger,<br>2 Earplugs, 4 pair communi-<br>cations<br>eartips, cord, 3 AA batteries: | 272 g                          |
| Weight Charger with batteries, 2 earpieces, and cord:  | 198 g                          |
| Weight: Charger  | 119 g                          |
| Weight: 1 earpiece:  | 4 g                            |

# **Environmental Characteristics**

| Storage temp (complete kit): | -20 to +50°C (-4°F to 122°F) |
|------------------------------|------------------------------|
| Earpiece Operating temp      | -20 to +50°C (-4°F to 122°F) |
| Charger Operating temp       | 0 to +50°C (32°F to 122°F)   |

# **Laboratory Attenuation**

### Ultrafit<sup>™</sup> Eartips

| Frequency (Hz)                | 125  | 250  | 500  | 1000 | 2000 | 4000 | 8000 |
|-------------------------------|------|------|------|------|------|------|------|
| Mean Attenuation (dB)         | 34,5 | 31,5 | 36,2 | 33,4 | 34,8 | 34,9 | 38,8 |
| Standard deviation (dB)       | 6,0  | 5,4  | 5,6  | 4,3  | 3,8  | 5,0  | 4,0  |
| Assumed Protection Value (dB) | 28,5 | 26,1 | 30,6 | 29,1 | 31,0 | 29,9 | 34,8 |

#### SNR=32 dB H=31 dB M=30 dB L=29 dB

## PELTIP5-01/Torque<sup>™</sup> Eartips (not incl.)

| •                             | · ·  | •    | •    |      |      |      |      |
|-------------------------------|------|------|------|------|------|------|------|
| Frequency (Hz)                | 125  | 250  | 500  | 1000 | 2000 | 4000 | 8000 |
| Mean Attenuation (dB)         | 37,8 | 36,0 | 40,5 | 41,2 | 41,3 | 39,6 | 46,1 |
| Standard deviation (dB)       | 4,3  | 5,5  | 4,2  | 4,7  | 3,2  | 4,3  | 3,6  |
| Assumed Protection Value (dB) | 33,5 | 30,5 | 36,3 | 36,5 | 38,0 | 35,3 | 42,5 |

SNR=38 dB H=37 dB M=36 dB L=34 dB

## **CCC-GRM-25** Eartips

| Frequency (Hz)                | 125  | 250  | 500  | 1000 | 2000 | 4000 | 8000 |
|-------------------------------|------|------|------|------|------|------|------|
| Mean Attenuation (dB)         | 35.5 | 32.5 | 37.1 | 38.0 | 37.6 | 39.5 | 45.5 |
| Standard deviation (dB)       | 4.5  | 4.0  | 4.4  | 3.7  | 2.9  | 4.6  | 4.2  |
| Assumed Protection Value (dB) | 30.9 | 28.4 | 32.7 | 34.3 | 34.6 | 34.9 | 41.3 |

SNR=36 dB H=35 dB M=34 dB L=32 dB

#### **∆WARNING**! Hearing Protection Products\*

These hearing protectors help reduce exposure to hazardous noise and other loud sounds. Misuse or failure to wear hearing protectors at all times that you are exposed to noise may result in hearing loss or injury. For proper use, see supervisor, User instructions, or call 3M Technical Service in hte U.S.A at 1-800-243-4630. If there is any drainage from your ear or you have an ear infection, consult with your physician before wearing earplugs. Failure to do so may result in hearing loss or injury.

Choking Hazard - Keep away from infants and small children.

CAUTION! When worn according to the User Instructions, this hearing protector helps reduce exposure to both continuous noises, such as industrial noises and noises from vehicles and aircraft, as well as very loud impulse noises, such as gunfire. It is difficult to predict the required and/or actual hearing protection obtained during exposure to impulse noises. For gunfire, the weapon type, number of rounds fired, proper selection, fit and use of hearing protection, proper care of hearing protection, and other variables will impact performance. If your hearing seems dulled or you hear a ringing or buzzing during or after any noise exposure (including gunfire), or for any other reason you suspect a hearing problem, your hearing may be at risk. To learn more about hearing protection for impulse noise, please visit www.3M.com/ hearing.

3M<sup>TM</sup> PELTOR<sup>TM</sup> Global Marketing Communication, Värr

rev. a

DS17001

**3M Personal Safety Division** 3M Svenska AB, Box 2341 SE-331 02 Värnamo Sweden Internet: www.3M.com/PELTOR Please recycle. Printed in Sweden. © 3M 2016. All rights reserved. 3M, UltraFit, and Torque are trademarks of 3M Company, used under license in Canada. PELTOR is a trademark of 3M Svenska AB, used under license in Canada.

#### Warranty:

The warranty does not cover any damage caused by neglected maintenance or careless handling. For more information on maintenance, please see the user instruction. For complete warranty condition, contact your dealer or local 3M office

#### ortant Notice

Important Notice 3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.