



Wireless two-way 6 mm (0.24") articulating camera with 1 m (3.3') probe with macro short focus

P/N: VSA2-1M-W

Copyright

© 2014, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: VSA2-1M-W

Release:

Commit: 18096

Language: en-US

Modified: 2014-10-02

Formatted: 2014-10-02

Corporate Headquarters

FLIR Systems, Inc.

27700 SW Parkway Ave.

Wilsonville, OR 97070

USA

Telephone: +1-503-498-3547

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



| | |
|-------------------------------|--|
| Part No. | VSA2-1M-W |
| General information | |
| Short description | Wireless two-way 6 mm (0.24") articulating camera with 1 m (3.3') probe with macro short focus |
| Compatible main unit | VS70 |
| Integrated handset | Yes |
| Wireless capabilities | 2.4 GHz to main unit |
| Compatible wireless handset | N/A |
| Compatible detachable cameras | N/A |
| Warranty | 2 years |
| Camera specifications | |
| Articulation | Two-way 240 ± 20° manual tip articulation |
| Diameter | 6 mm |
| Resolution | VGA (640 × 480 pixels) |
| Probe length | 1 m |
| Focal length | 20–60 mm |
| Field of view | 56° |
| Imaging sensor | CMOS |
| Video format | NTSC |
| Brightness control | Manual with variable options |
| Lamp type | LED |
| Power system | |
| Power requirements | Integrated rechargeable battery |
| Run time | 2 hours continuous use |
| Auto power off | No |
| Power adapter | 100–240 V input/5 V DC output |
| Environmental data | |
| Operating temperature | –10 to 50°C (14–122°F) |
| Operating humidity | 80% maximum |
| Storage temperature | –40 to 80°C (–40 to 176°F) |



Wireless two-way 6 mm (0.24") articulating camera with 1 m (3.3') probe with macro short focus

P/N: VSA2-1M-W

© 2014, FLIR Systems, Inc.

#VSA2-1M-W; r. /18096; en-US

| Physical data | |
|----------------------------------|---|
| Weight | 0.43 kg (0.95 lb.) |
| Dimensions (H × W × L) | 190 mm × 70 mm × 63.5 mm (7.5" × 2.75" × 2.5") |
| Material | PC-ABS, rubber hand grip, nylon strap |
| Color | Gray, black |
| Shipping information | |
| Packaging type | White box with FLIR accessory printing |
| Packaging contents | White box with FLIR accessory graphic, VSA2-1M-W, camera attachments: mirror, anti-snag tip, magnet |
| Packaging weight | 1.3 kg |
| Packaging dimensions (H × W × L) | 43 cm × 37 cm × 7.5 cm |
| Carton weight | 6.2 kg |
| Carton dimensions (H × W × L) | 45 cm × 31 cm × 39 cm |
| Carton quantity | 4 |
| EAN-13 | 7332558007501 |
| UPC-12 | 793950400807 |
| Country of origin | TW |
| Tariff code | 9013909000 |
| Technical support | |
| Website | http://support.flir.com |
| E-mail | T&Msupport@flir.com |
| Phone | 855-499-3662 |
| Repairs | repair@flir.com |