



Wireless two-way 6 mm (0.24") articulating camera with 2 m (78") probe with short macro focus

P/N: VSA2-2M-W

Copyright

© 2014, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: VSA2-2M-W

Release:

Commit: 18096

Language: en-US

Modified: 2014-10-02

Formatted: 2014-10-02

Corporate Headquarters

FLIR Systems, Inc.

27700 SW Parkway Ave.

Wilsonville, OR 97070

USA

Telephone: +1-503-498-3547

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



Part No.	VSA2-2M-W
General information	
Short description	Wireless two-way 6 mm (0.24") articulating camera with 2 m (78") probe with short macro focus
Compatible main unit	VS70
Integrated handset	Yes
Wireless capabilities	2.4 GHz to main unit
Compatible wireless handset	N/A
Compatible detachable cameras	N/A
Warranty	2 years
Camera specifications	
Articulation	Two-way 240 ± 20° manual tip articulation
Diameter	6 mm
Resolution	VGA (640 × 480 pixels)
Probe length	2 m
Focal length	20–60 mm
Field of view	56°
Imaging sensor	CMOS
Video format	NTSC
Brightness control	Manual with variable options
Lamp type	LED
Power system	
Power requirements	Integrated rechargeable battery
Run time	2 hours continuous use



Wireless two-way 6 mm (0.24") articulating camera with 2 m (78") probe with short macro focus

P/N: VSA2-2M-W

© 2014, FLIR Systems, Inc.

#VSA2-2M-W; r. /18096; en-US

Power system	
Auto power off	No
Power adapter	100–240 V input/5 V DC output
Environmental data	
Operating temperature	–10 to 50°C (14–122°F)
Operating humidity	80% maximum
Storage temperature	–40 to 80°C (–40 to 176°F)
Physical data	
Weight	0.43 kg (0.95 lb.)
Dimensions (H × W × L)	190 mm × 70 mm × 63.5 mm (7.5" × 2.75" × 2.5")
Material	PC-ABS, rubber hand grip, nylon strap
Color	Gray, black
Shipping information	
Packaging type	White box with FLIR accessory printing
Packaging contents	White box with FLIR accessory graphic, camera, camera attachments: mirror, anti-snap tip, magnet
Packaging weight	1.4 kg
Packaging dimensions (H × W × L)	43 cm × 37 cm × 7.5 cm
Carton weight	6.5 kg
Carton dimensions (H × W × L)	45 cm × 31 cm × 39 cm
Carton quantity	4
EAN-13	7332558007563
UPC-12	793950400845
Country of origin	TW
Tariff code	9013909000
Technical support	
Website	http://support.flir.com
E-mail	T&Msupport@flir.com
Phone	855-499-3662
Repairs	repair@flir.com