

Prelude



230V, 50Hz, Class I, IP44*

0,5 - 1,0 mm² 8 mm
 1,5 - 2,5 mm² 12 mm
 ca 10° (max. 20°

Max 16A

	A	B	C	D
15W	72.5mm	334mm	87.5mm	494mm
15W *	160.5mm	335mm	102.5mm	598mm
18W	73mm	486.5mm	87.5mm	647mm
18W *	146mm	487.5mm	87.5mm	721mm
14W	72.5mm	446mm	87.5mm	606mm
24W				
14W *	145.5mm	447mm	87.5mm	680mm
24W *				

* NO: Med stikkontakt
EN: With outlet
FR: Avec prise
NL: Met stopcontact
DE: Mit stopcontact

* IP44

* IP20

NO: Skadet skjerm må erstattes med ny.
EN: Replace any cracked protective shield.
FR: Tout diffuseur endommagé doit être remplacé.
NL: Gebroken lens moet vervangen worden.
DE: Beschädigte Leuchten-Abdeckungen müssen ausgetauscht werden.

* NO: Med stikkontakt
EN: With outlet
FR: Avec prise
NL: Met stopcontact
DE: Mit stopcontact

Rev. 17.12.2012

SG Armaturen AS
Svåbekk Industriområde
N-4790 Lillesand
NORGE
Tel: +47 37 26 84 84
www.sg-as.no

SG Armaturen AB
August Barksg. 30B
SE-421 32 Västra Frölunda
SVERIGE
Tel: +46 31 81 71 10
www.sg-ab.se

SG Lighting SA/NV
Wayenborgstraat 4
B-2800 Mechelen Noord II
BELGIQUE/BELGIË
Tel: +32 (0) 15 20 72 71
www.sglighting.net

SG Lighting SA/NV
Parc de l'Arboretum
73 rue de Saint Mandrier
83140 Six Fours Les Plages
FRANCE
Tel: +33 04 94 93 00 00
www.sglighting.net

SG Leuchten GmbH
Nordstrasse 53
D-59399 Olfen
DEUTSCHLAND
Tel: 0152-57000500
www.sg-leuchten.de