



 PRODUCT-DETAILS

20 EUCB2USB-214-510

Socket insert Safety Shutter with USB A/A white - Jussi



General Information

Extended Product Type:	20 EUCB2USB-214-510
Product ID:	2CKA002011A6265
EAN:	4011395303672
Catalog Description:	Socket insert Safety Shutter with USB A/A white - Jussi
Long Description:	For connecting electric loads. DP (2 P + E) With screwless terminals. For supply and support of mobile devices via USB-cable. With two USB type A outputs. Simultaneous charging via USB connection and use of the SCHUKO® socket outlet. Support of loading protocol on the USB-A connection: Apple MFI with 2.4 A and BC 1.2 with 1.5 A. With electronic short-circuit protection. With electronic overload protection.
Display Name:	20 EUCB2USB-214-510

Installation

Instructions and Manuals:	No document needed
Mounting Type:	Flush Mounted
Type of Fastening:	Mounting with Claw Mounting with Screw

Modular Components Included: Cover with Flush Mounted Insert and Mounting Plate

Environmental

Ambient Air Temperature:	Operation 5 ... +35 °C
Degree of Protection:	IP20

Technical

Data Sheet, Technical Information:	No document needed
Function:	USB with enhanced contact protection
Number of Poles:	2P+PE
Number of Phases:	1-phase
Number of Outputs:	USB-A 2
Connection Type:	USB
Socket Outlet Type:	Protective Contact (SCHUKO)
Options Available:	Safety Shutter
Terminal Type:	Screwless Terminals
Safety Function Option:	Safety Shutter
USB Port Type:	USB A/A
Charging Protocol:	Apple MFi 2.4 A BC 1.2 DCP

Electrical

Rated Voltage (U_r):	230 V AC
Secondary Voltage:	5 V
Rated Current (I_n):	16 A
Secondary Current:	2.4 A -empty-
Rated Frequency (f):	50/60 Hz
Power Loss:	0.075 W
Power Watt:	Maximum DC 12 W

Design

Design Range:	Jussi
Surface Finishing:	Untreated Glossy
Material:	Thermoplastic
Label Space Provided:	Without Label Space
RAL Number:	Similar to RAL 9010

Color:	white
Number of Gangs:	1-gang

Dimensions

Product Net Width:	71 mm
Product Net Height:	71 mm
Product Net Depth / Length:	75 mm
Product Net Weight:	114.5 g
Built-In Depth (t₂):	39.5 mm

Ordering

Replacement Product ID (NEW):	2CKA002011A6297
Replaced Product ID (OLD):	2CKA002011A6175
E-Number (Finland):	2506184
E-Number (Norway):	1517904
E-Number (Sweden):	1815425

Material Compliance

RoHS Declaration:	2CKA200000E7232
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration:	2CKA309999E9999
REACH Information:	True - contains substances > 0.1 mass percentage
REACH Date:	20260216
Conflict Minerals Reporting Template (CMRT):	9AKK108468A3363
SCIP:	Od20669e-1faa-4e00-927e-38deaf6c7949 Germany
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B:	Business To Consumer

Certificates and Declarations

Declaration of Conformity - CE:	2CKA100000E4419
EU Data Act Applicability and Compliance:	Not Applicable

External Classifications and Standards

ETIM 9:	EC000125 - Socket outlet
ETIM 10:	EC000125 - Socket outlet
eClass:	V11.0 : 27144042

Categories

Products > Low Voltage Products and Systems > Wiring Accessories - Electronic Devices > USB Chargers > Socket Outlets with USB

Products > Low Voltage Products and Systems > Wiring Accessories - Light Switch Ranges > Cover Plates and Control Elements > Socket Outlets

